



# MINERAL SHOCK FLUID

Released: 2015-07-10

Version: 1.2  
Revision Date: 2024-09-03

## 1. IDENTIFICATION OF THE SUBSTANCE / APPLICATION AND THE COMPANY

**Supplier:**Maxima Racing Oils  
9266 Abraham Way  
Santee, CA 92071  
USA  
+1 619 449 5000**Product Name:** Racing Shock Fluid  
Light 3 wt, Medium 7 wt, Heavy 10 wt**Applications:** Hydraulic Suspension Oil**Emergency Telephone:** In USA: CHEMTREC +1 703 527 3887 (24 hours)  
Outside USA: +1 619 449 5000

## 2. HAZARDS IDENTIFICATION

**GHS Classification**

Aspiration Toxicity Category 1

**GHS Pictogram****Signal Word****Danger!****Hazard Statements**

H304 May be fatal if swallowed and enters airways.

**Precautionary Statements****Prevention** None**Response** P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 Do NOT induce vomiting.

**Storage** P405 Store locked up.**Disposal** P501 Dispose of contents and container in accordance with local and national regulations.**Other Hazards**

None

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Components**

Petroleum Distillates

**Content %**

60-90

**CAS Number**

64742-54-7



# MINERAL SHOCK FLUID

Released: 2015-07-10

Version: 1.2  
Revision Date: 2024-09-03

Polyalkylacrylate	10-20	64742-48-9
Zinc dialkyl dithiophosphate	<1	Mixture
		Proprietary

The specific identity and/or exact percentage has been withheld as a trade secret.

## 4. FIRST-AID MEASURES

<b>Inhalation</b>	If inhaled remove to fresh air. If irritation or difficulty in breathing occurs, get medical attention.
<b>Skin Contact</b>	Wash skin with soap and water. Remove clothing and shoes if contaminated. Launder clothing before reuse. If irritation develops, get medical attention.
<b>Eye Contact</b>	Flush eyes with water. Remove contact lenses, if present and easy to do so. If eye irritation persists, get medical attention.
<b>Ingestion</b>	If conscious, rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention.
<b>Most Important Symptoms</b>	May cause mild eye irritation. Prolonged skin contact may cause irritation. Inhalation of vapors or mists may cause respiratory irritation. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration during swallowing or vomiting may cause lung damage.
<b>Indication of Immediate Medical Attention Needed</b>	Immediate medical attention is required if ingested.
<b>Notes to Physician</b>	Treat appropriately

## 5. FIRE FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Use water fog, foam, dry chemical or carbon dioxide (CO <sub>2</sub> ) to extinguish flames.
<b>Specific Hazards Arising From The Chemical</b>	This material will burn although it is not easily ignited. Combustion will produce carbon oxides and unidentified organic compounds.
<b>Special Protective Equipment And Precautions For Fire-Fighters</b>	Firefighters should wear full emergency equipment and a NIOSH approved positive pressure self-contained breathing apparatus. Cool exposed intact containers with water.

## 6. ACCIDENTAL RELEASE MEASURES



## MINERAL SHOCK FLUID

Released: 2015-07-10

Version: 1.2  
Revision Date: 2024-09-03

<b>Personal Precautions</b>	Wear appropriate protective equipment. Wash thoroughly after handling. See also: "Personal Protection "section 8.
<b>Environmental Hazards</b>	Avoid release into the environment. Report spill as required by local and federal regulations.
<b>Methods/Materials for Cleaning up</b>	Dike spill and collect with an inert absorbent. Place into closable containers for disposal. Collected material is handled in accordance with section 13 "Disposal Considerations".

### 7. HANDLING AND STORAGE

<b>Precautions for Safe Handling:</b>	Avoid contact with eyes, skin and clothing. Avoid breathing vapors and mists. Wash thoroughly after handling. Remove oil-soaked clothing and launder before re-use.
<b>Conditions for Safe Storage</b>	Store in a cool area away from oxidizing agents. Protect containers from physical damage.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Exposure Limits</b>	Petroleum Distillates	5 mg/m <sup>3</sup> TWA OSHA PEL (as oil mist) 5 mg/m <sup>3</sup> TWA ACGIH TLV (inhalable) (as mineral oil)
	Polyalkylacrylate	None Established
	Zinc dialkyl dithiophosphate	None Established
<b>Appropriate Engineering Controls</b>	Good general room ventilation (equivalent to outdoors) should be adequate under normal conditions. If exposures are excessive, increased mechanical ventilation such as local exhaust may be required.	
<b>Personal Protection</b>		
<b>Respiratory Protection:</b>	None needed under normal use conditions with adequate ventilation. If exposure limits are exceeded, use a NIOSH approved respirator with organic vapor cartridges and particulate pre-filter. Selection of respiratory protection depends on the contaminant type, form and concentration. Select in accordance with OSHA 1910.134 and good Industrial Hygiene practice.	
<b>Eye Protection:</b>	Safety glasses or goggles recommended if splashing is possible.	
<b>Skin/Body Protection:</b>	If there is a potential for skin contact, wear a long sleeved shirt and apron. Neoprene or nitrile rubber boots when necessary to avoid contaminating shoes.	
<b>Hand Protection:</b>	Use nitrile or neoprene gloves recommended to prevent skin contact.	



## MINERAL SHOCK FLUID

Released: 2015-07-10

Version: 1.2  
Revision Date: 2024-09-03

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Liquid
<b>Color</b>	Red
<b>Odor</b>	Petroleum odor
<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available
<b>Freezing Point</b>	No data available
<b>Boiling Point</b>	No data available
<b>Flash Point</b>	378°F (190°C) (COC)
<b>Evaporation Rate</b>	No data available
<b>Flammability (solid, gas)</b>	No data available
<b>Upper Explosion Limit</b>	No data available
<b>Lower Explosion Limit</b>	No data available
<b>Vapor Pressure</b>	<0.01 mmHg @ 100°F
<b>Vapor Density (Air=1)</b>	>1
<b>Relative Density</b>	0.84 – 0.86 @ 15.0°C
<b>Solubility</b>	Soluble in hydrocarbons; insoluble in water
<b>Partition Coefficient: n-octanol/water</b>	No data available
<b>Auto Ignition Temperature</b>	No data available
<b>Decomposition Temperature</b>	No data available
<b>Volatile Organic Compounds (VOC)</b>	0%
<b>Viscosity</b>	13.9 cSt @ 40°C

### 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	Not expected to be reactive.
<b>Chemical Stability</b>	Stable.
<b>Possibility of Hazardous Reactions</b>	None known.
<b>Conditions to Avoid</b>	None known.
<b>Incompatible Materials</b>	Avoid contact with strong oxidizing agents.
<b>Hazardous Decomposition Product</b>	Thermal decomposition may produce carbon oxides and unidentified organic compounds.



## MINERAL SHOCK FLUID

Released: 2015-07-10

Version: 1.2  
Revision Date: 2024-09-03

### 11. TOXICOLOGICAL INFORMATION

#### Potential Health Hazards

**Eye Contact:** May cause mild eye irritation with redness and tearing.

**Skin Contact:** Prolonged skin contact may cause irritation dryness.

**Inhalation:** Excessive inhalation of vapors or mists may cause upper respiratory tract irritation and central nervous system effects including headache, dizziness and nausea.

**Ingestion:** Swallowing large amounts may cause gastrointestinal effects including nausea and diarrhea. Aspiration during swallowing or vomiting may cause lung damage.

**Chronic Effects of Overexposure:** None known.

**Sensitization:** None of the components have been shown to cause sensitization in animals or humans.

**Mutagenicity:** This product is not expected to cause mutagenic activity.

**Reproductive Toxicity:** This product is not expected to cause reproductive or developmental effects.

**Carcinogenicity:** None of the components of this product are listed as a carcinogen or suspected carcinogen by IARC, NTP, or OSHA.

#### Acute Toxicity:

Petroleum Distillates	Oral rat LD50 >5000 mg/kg, Dermal rabbit LD50 >5000 mg/kg
Polyalkylacrylate	Oral rat LD50 >5000 mg/kg, Dermal rabbit LD50 >2000 mg/kg
Zinc dialkyl dithiophosphate	Oral rat LD50 >5000 mg/kg, Dermal rabbit LD50 >2000 mg/kg

### 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Petroleum Distillates	96 hr LC50 fish >100 mg/L, 48 hr EC50 daphnia magna >100 mg/L, 72 hr LC50 algae >100 mg/L
Polyalkylacrylate	96 hr LC50 fish >100 -1000 mg/L
Zinc dialkyl dithiophosphate	96 hr LC50 fish 1-10 mg/L, 48 hr EC50 daphnia magna 1-10 mg/L, 72 hr LC50 algae 10-100 mg/L

<b>Biodegradation</b>	Petroleum distillates are inherently biodegradable.
<b>Bioaccumulation</b>	Petroleum distillates has the potential to bioaccumulate.
<b>Mobility in soil</b>	No data available
<b>Other adverse effects:</b>	None known.

### 13. DISPOSAL CONSIDERATIONS

**Disposal** Dispose in accordance with all local, state and federal regulations.



## MINERAL SHOCK FLUID

Released: 2015-07-10

Version: 1.2  
Revision Date: 2024-09-03

### 14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT		Not Regulated			
TDG		Not Regulated			
IMDG		Not Regulated			
IATA		Not Regulated			

**Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not applicable – product is transported only in packaged form

**Special precautions:** None known.

### 15. REGULATORY INFORMATION

**CERCLA:** This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**EPA SARA 302:** This product does not contain chemicals regulated under SARA Section 302.

**EPA SARA 311 Hazard Classification:** Acute Health.

**EPA SARA 313:** This product contains the following chemicals that are regulated under SARA Title III, section 313:

Zinc Compounds	Proprietary	<1
Zinc dialkyl dithiophosphate		

**California Proposition 65:** This product contains the following chemicals known to the State of California to cause cancer and reproductive toxicity:



## MINERAL SHOCK FLUID

Released: 2015-07-10

Version: 1.2

Revision Date: 2024-09-03

Ethyl acrylate	140-88-5	<1ppm	cancer
Propylene oxide	75-56-9	<1ppm	cancer
Ethylene oxide	75-21-8	<1ppm	cancer / developmental
1, 4 dioxane	123-91-1	<1ppm	Cancer

### Chemical Inventories

**Toxic Substances Control Act:** All of the components of this product are listed on the TSCA inventory

### 16. OTHER INFORMATION

NFPA Rating (NFPA 704):	Health: 1	Fire: 1	Instability: 0
HMIS Rating:	Health: 1	Fire: 1	Physical Hazard: 0

Date of Revision: September 3, 2024

Date of Previous Revision: November 6, 2017

Revision History:

7/10/15: Converted to GHS format. All section revised

11/6/17: Updated emergency telephone #

9/3/24: Reviewed all sections to ensure they are up to date.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.